



ECOSTICKÂ® 1816B

Description/Nature of the product

Acqueous dispersion of a polymer based on polyurethane modified, ca.50%

Application by

Spray gun, roller machine

Characteristics

Water based adhesive ideal for coupling leather, eco-leather, fabrics, covers, cardboards. Ideal for gluing PVC, EVA, nylon and ready made rubbers. Ideal for gluing greasy leather with presence of grease up to 15%.

Instructions for use

Apply ECOSTICKÂ® 1816B on both sides. Let it dry. To work without preheating the adhesive, couple both sides within 20 minutes after drying and press. Otherwise, if this time is exceeded, reactivate at a 60°-70°, couple and press. The adhesive can be applied on one side to couple leather with textiles, moltoprene, foam rubber: apply plenty of ECOSTICKÂ® 1816B on leather or on material not so absorbing and couple immediately.

Open Time

Cold bonding: up to 20 min. after the adhesive is dried. Reactivation by heating: within 48 hours.

Remarks



Intercom Srl ® - P.iva e C.F. 06183210480

Address: Via della Gora, 13 - 50025 Montespertoli - Firenze - Italia

Phone: +39 0571 671096 - **Fax:** +39 0571 671151 - **Email:** info@intercomsas.it - **Web:** www.intercomsas.it