

Item description: A5.300

## Bonding system with conveyor belt 300 cm and dryer, assembled and installed

Automatic bonding system, equipped with insulated drying tunnel adjustable from 120cm up to 170cm with hot air and temperatures adjustable up to 110 degrees with circulation of internal air to minimize the consumption, spray gun model G9 whose jet can be adjusted from a cone shape of 15mm up to a knife shape of 200mm, conveyor belt 300 cm adjustable, intake and Teflon stainless steel adhesive tank 10 lt. capacity.

On request, it is possible to add a second spray gun on the axle in order to use different kind of adhesives and or one or more manual spray guns.



The operator places the materials on the padded carpet of the conveyor belt which automatically brings the materials under the spray gun where the adhesive is applied in an uniform way. Afterwards the materials go inside the drying tunnel for a quick drying of adhesive under any climatic condition. At the tunnel exit the materials are ready to be coupled. Thanks to this system the materials are not displaced so there are not idle times due to the manual management of these working phases. The powerful intake prevents even the most light materials from moving due to the air coming out from the spray gun and at the same time it avoids the pulverized particles of adhesive to spread around the machine.

## Specific:

Capacity m3 / h : 3050	Volt : 400 Vac	Prevalence : 53	Hertz : 50
Watt : 4500	Bar exercise : 7	Decibel (dB): 79	Ampere: 8,4
Air It / min : 180 - 200	Effective width cm : 100	Usable depth cm : 70	Average consumption : 3 Kw
Gross Weight kg: 400.000	Tare Kg : .000	Length mt : 3.146	Height mt : 1.95
Net Weight kg: 400.000	Net Weight kg:	mt Width: 1.4	Volume m3 : 8.588

Intercom Srl ® - P.iva e C.F. 06183210480

Address: Via della Gora, 13 - 50025 Montespertoli - Firenze - Italia

Phone: +39 0571 671096 - Fax: +39 0571 671151 - Email: info@intercomsas.it - Web: www.intercomsas.it