

Vacuum bench B12 spraying system S8 and tank CO

Item I1288

The machine is composed by: - Vacuum bench B12 with air outlet upwards, equipped with led light and a silent and powerful engine, with an automatic air control system that increases and decreases the intake power depending on the level of filter cleaning. Also equipped with alarm light. that suggests the replacement of the filter. -Spray gun G6 designed for both precise and large areas bonding (spraying from a minimum of 3 mm up to a maximum of 50 mm) -Stainless steel tank 5lt. capacity, treated with non-stick Teflon.



The operator, after starting the machine, can place the materials on the working plane so to make maximum use of the intake on the working plane for both keeping the materials standing and absorbing the nebulized adhesive. All the spray gun functions can be adjusted: quantity of adhesive, width of jet and quality of distribution even on different thicknesses. For a proper functioning of the vacuum bench it is recommended to replace the filter each time is visibly dirty and/or when the warning led is on. To speed up the working process it is possible to use some nets in order to reduce the idle time due to loading and unloading the pieces on the working area. A jet of air immediately before and after the adhesive nebulization keeps the nozzle constantly clean. Our systems are maintenance free. The tank is conceived in a way that allow the use of the adhesive in bag in box avoiding to make dirty the tank and to filter the glue thus preventing the contact with air which can alter its properties.

Technical Data:

29/07/2022

Capaciy m3/h: 2600	Volt: 220/240	Pressure head: 680	Air (lt/min): 30	Bar: 6
Decibel: 76	Watt: 1040	Hertz: 50/60	Ampere: 4,5	Average Consumption: 1040
Gross Weight: 150,9	Tare (kg): 18,4	Lenght (mt): 0,8	Height (mt): 1,8	Volume (m3): 0
Net Weight: 132,5		Width: 1,2	Working surface (cm): 120 x 55	