

Intercom S.R.L. Via della Gora, 13 50025 Montespertoli FI Cod.Fisc. - P.Iva 06183210480 - REA 607410 info@intercomsas.it www.intercomsas.it Cap.sociale € 50.000 int.vers. Tel. +39 0571 671096 - Fax +39 0571 671151

## Vacuum bench B14 spraying system S8 and tank CO

## Item I1488

New bench entirely closed equipped with LED light and a powerful aspiration motor which guarantee a constant intake and the total absence of fine particles of adhesive around the machine. Spray gun G6 designed for both precise and large areas bonding. In particular it is possible to spray the glue from a minimum of 3 mm up to a maximum of 50 mm. Stainless steel tank for 5 kg bags treated with nonstick Teflon. The structure is conceived in a way that it will be possible, later on, to install the automatic moving and drying parts. In this way even small companies can afford an investment to optimize the bonding phases without losing the previous investment. It is also possible to add a second aspirator. It is possible to add a second spraying gun on the shaft so to be able to use different kind of adhesives and/or one or more manual spraying guns. Following the new changes made, the air outlet is directly upwards.



The operator, after starting the machine, can place the materials on theworking plane so to make maximum use of the intake on the working plane for both keeping the materials standing and absorbing the nebulized adhesive. All the spray gun functions can be adjusted: quantity of adhesive, width of jet and quality of distribution even on different thicknesses. For a proper functioning of the vacuum bench it is recommended to replace the filter each time is visibly dirty and/or when the warning light turns on. To speed up the working process it is possible to use some nets in order to reduce the idle time due to loading and unloading the pieces on the working area. A jet of air immediately before and after the adhesive nebulization keeps the nozzle constantly clean. Our systems are maintenance free. The tank is conceived in a way that allow the use of the adhesive in bag in box avoiding to make dirty the tank and to filter the glue thus preventing the contact with air.

## **Technical Data:**

17/07/2023

Capaciy m3/h: 3800	Volt: 400	Pressure head: 1200	Air (lt/min): 30	Bar: 6
Decibel: 78	Watt: 2150	Hertz: 50-60	Ampere: 3,34	Average Consumption: 2150
Gross Weight: 270	Tare (kg): 10	Lenght (mt): 1,2	Height (mt): 2	Volume (m3): 0
Net Weight: 260		Width: 2,2	Working surface (cm): 192 x 105	